




Cardiotensor: A Python Library for Orientation Analysis and Tractography in 3D Cardiac Imaging

Joseph Brunet^{1,2}, Lisa Chestnutt³, Matthieu Chourrout¹, Hector Dejea², Vaishnavi Sabarigirivasan², Peter D. Lee^{1,4}, and Andrew Cook³

¹ Department of Mechanical Engineering, University College London, London, UK ² European Synchrotron Radiation Facility, Grenoble, France ³ UCL Institute of Cardiovascular Science, London, UK ⁴ Research Complex at Harwell, Didcot, UK

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

Software

- [Review](#) 
- [Repository](#) 
- [Archive](#) 

Editor: [Open Journals](#) 

Reviewers:

- [@openjournals](#)

Submitted: 01 January 1970

Published: unpublished

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

Summary

Understanding the architecture of the human heart requires analyzing its microstructural organization across scales. With the advent of high-resolution imaging techniques such as synchrotron-based tomography, it has become possible to visualize entire hearts at micron-scale resolution. However, translating these large, complex volumetric datasets into interpretable, quantitative descriptors of cardiac organization remains a major challenge. Cardiotensor is an open-source Python package designed to quantify 3D cardiomyocyte orientation in whole- or partial-heart imaging datasets. It provides efficient, scalable implementations of structure tensor analysis, enabling extraction of directional metrics such as helix angle (HA), transverse angle (TA), and fractional anisotropy (FA). The package supports datasets reaching teravoxel-scale and is optimized for high-performance computing environments, including parallel and chunk-based processing pipelines. In addition, cardiotensor includes tractography functionality to reconstruct continuous cardiomyocyte trajectories. This enables fiber-level visualization and structural mapping of cardiac tissue, allowing detailed assessments of anatomical continuity and regional organization.

Statement of Need

Despite major advances in high-resolution 3D imaging, there is a lack of open-source tools to analyze cardiomyocyte orientation in large volumetric datasets. Most established frameworks were developed for diffusion tensor MRI (DT-MRI), where orientation is inferred from water diffusion. Examples include MRtrix3 (Tournier et al., 2019), DIPY (Garyfallidis et al., 2014), and DSI Studio (Yeh, 2025). While powerful for diffusion-based neuro and cardiac applications (Mekkaoui et al., 2017), these packages are not designed to handle direct image-gradient-based orientation estimation or the teravoxel-scale datasets produced by synchrotron tomography, micro-CT, or 3D optical microscopy.

For non-diffusion imaging modalities, researchers have historically relied on custom structure tensor implementations to estimate fiber orientation directly from image intensity gradients. However, most of these are in-house codes, often unpublished or not generalizable. For example, structure tensor analysis has been applied in the heart using micro-CT (Reichardt et al., 2020), microscopy (Dileep et al., 2023; Garcia-Canadilla et al., 2022), and synchrotron tomography (Dejea et al., 2019), but these methods were tailored to specific datasets and lacked scalability or public availability.

Cardiotensor addresses this gap by providing an open-source Python package specifically tailored to structure tensor analysis of large cardiac volumes. Rather than relying on diffusion

modeling, cardiotorus infers tissue orientation directly from image intensity gradients, making it applicable across a wide range of modalities. Previous studies have demonstrated strong agreement between structure tensor-based orientation and DT-MRI-derived metrics when applied to the same human hearts (Teh et al., 2016). The package supports full pipelines from raw image stacks to fiber orientation maps and tractography. Its architecture is optimized for large datasets, using chunked and parallel processing suitable for high-performance computing environments.

Cardiotorus has already been successfully applied in published work to characterize 3D cardiomyocyte architecture in healthy and diseased human hearts using synchrotron tomography (Brunet et al., 2024) to datasets over a terabyte in size. While cardiotorus was conceived for cardiac imaging, the package is modality- and tissue-agnostic. Any volumetric dataset exhibiting coherent fibrous microstructure can be analyzed, including brain white matter, skeletal muscle, and tendon. This generality makes the library useful for both cardiovascular and broader anatomical or histological studies.




Figure 1: Cardiotorus pipeline for 3D cardiac orientation analysis and tractography. (a) Input whole- or partial-heart volume with optional myocardial mask. (b) Local cardiomyocyte orientation estimated via 3D structure tensor and eigenvector decomposition. The third eigenvector field (smallest eigenvalue) is visualized as arrows color-coded by helix angle (HA); inset shows septal fiber rotation. (c) Transformation to a cylindrical coordinate system enables computation of voxel-wise helix angle (HA), transverse angle (TA), and fractional anisotropy (FA) maps. (d) Streamline tractography reconstructs continuous cardiomyocyte trajectories, color-coded by HA.

Implementation

Cardiotorus is implemented in pure Python and designed to efficiently process very large 3D cardiac imaging datasets. It relies primarily on NumPy (Van Der Walt et al., 2011) for numerical computation, with I/O accelerated by tiffle (Gohlke, 2025), Glymur (Evans, 2025), and OpenCV (Bradski, 2000). Dask (Rocklin, 2015) is used exclusively to parallelize file reading, while the core computations rely on Python's multiprocessing module for local parallelism. The package builds on the structure-tensor library (Jeppesen et al., 2021) to calculate the 3D structure tensor and eigenvector decomposition.

The package supports multiple use cases:

- Command-line workflows, which automate batch processing from a configuration file of terabyte-scale heart volumes and produce results as live plots or files saved to disk.
- Embedded use in larger Python analysis workflows, enabling flexible scripting and scalable execution on cluster environments.

Efficient computation is achieved through a chunk-based processing strategy with padding, which avoids edge artifacts. This architecture allows parallelization across computing clusters by splitting volumes into independent jobs, enabling cardiotensor to process whole-heart volumes in hours rather than days while maintaining practical memory requirements.

Architecture

Cardiotensor is organized into five main modules, designed for clarity and scalability:

- **orientation**: Computes local cardiomyocyte orientation using a chunked 3D structure tensor pipeline, including eigenvalue decomposition, cylindrical coordinate rotation, and calculation of helix angle (HA), transverse angle (TA), and fractional anisotropy (FA).
- **tractography**: Generates and filters streamlines tracing cardiomyocyte trajectories from the orientation field for fiber-level reconstruction and analysis.
- **analysis**: Provides a GUI for regional quantification and plotting transmural profile.
- **visualization**: Supports interactive 3D visualization of vector fields and streamlines, HA color-coding, and export to VTK/ParaView for large-scale rendering.
- **utils**: Contains general utilities for I/O, image preprocessing, configuration parsing, and vector math, supporting the entire pipeline.

This modular architecture ensures reproducibility, maintainability, and easy integration into larger cardiac imaging workflows.

Documentation and Usage

The documentation for cardiotensor is available online at:

<https://josephbrunet.github.io/cardiotensor>

The main components of the documentation are:

- Step-by-step walkthroughs for installation, first steps, and a guided example covering all available commands. A small example dataset and its corresponding mask are provided with the package.
- In-depth explanations of the core algorithms used in cardiotensor, including structure tensor theory, helix angle calculation, fractional anisotropy (FA), and tractography integration.
- Reference guides for the command-line interface, configuration file format, and public API.

Acknowledgements

The authors would like to thank David Stansby for his guidance on the Python package structure, documentation framework, and best practices for scientific software development.

This project has been made possible in part by grant number 2022-316777 from the Chan Zuckerberg Initiative DAF, an advised fund of Silicon Valley Community Foundation. This work was also supported in part by the Wellcome Trust [310796/Z/24/Z].

The authors gratefully acknowledge ESRF beamtimes md1290 and md1389 on BM18 as sources of the data.

Peter D. Lee is a CIFAR MacMillan Fellow in the Multiscale Human program. This research is also based on work supported by a CIFAR Catalyst Award.

AC's research is enabled through the Noé Heart Centre Laboratories, which are gratefully supported by the Rachel Charitable Trust via Great Ormond Street Hospital Children's Charity (GOSH Charity). The Noé Heart Centre Laboratories are based in The Zayed Centre for

112 Research into Rare Disease in Children, which was made possible thanks to Her Highness
113 Sheikha Fatima bint Mubarak, wife of the late Sheikh Zayed bin Sultan Al Nahyan, founding
114 father of the United Arab Emirates, as well as other generous funders.

115 References

- 116 Bradski, G. (2000). The opencv library. *Dr. Dobb's Journal: Software Tools for the Professional*
117 *Programmer*, 25(11), 120–123.
- 118 Brunet, J., Cook, A. C., Walsh, C. L., Cranley, J., Tafforeau, P., Engel, K., Arthurs, O.,
119 Berruyer, C., Burke O'Leary, E., Bellier, A., Torii, R., Werlein, C., Jonigk, D. D., Ackermann,
120 M., Dollman, K., & Lee, P. D. (2024). Multidimensional Analysis of the Adult Human
121 Heart in Health and Disease Using Hierarchical Phase-Contrast Tomography. *Radiology*,
122 312(1), e232731. <https://doi.org/10.1148/radiol.232731>
- 123 Dejea, H., Garcia-Canadilla, P., Cook, A. C., Guasch, E., Zamora, M., Crispi, F., Stampanoni,
124 M., Bijnens, B., & Bonnin, A. (2019). Comprehensive Analysis of Animal Models of
125 Cardiovascular Disease using Multiscale X-Ray Phase Contrast Tomography. *Scientific*
126 *Reports*, 9(1), 6996. <https://doi.org/10.1038/s41598-019-43407-z>
- 127 Dileep, D., Syed, T. A., Sloan, T. F., Dhandapany, P. S., Siddiqi, K., & Sirajuddin, M. (2023).
128 Cardiomyocyte orientation recovery at micrometer scale reveals long-axis fiber continuum
129 in heart walls. *The EMBO Journal*, 42(19), e113288. [https://doi.org/10.15252/embj.](https://doi.org/10.15252/embj.2022113288)
130 [2022113288](https://doi.org/10.15252/embj.2022113288)
- 131 Evans, J. G. (2025). *Quintusdías/glymur*. <https://github.com/quintusdias/glymur>
- 132 Garcia-Canadilla, P., Mohun, T. J., Bijnens, B., & Cook, A. C. (2022). Detailed quantification
133 of cardiac ventricular myocardial architecture in the embryonic and fetal mouse heart
134 by application of structure tensor analysis to high resolution episcopic microscopic data.
135 *Frontiers in Cell and Developmental Biology*, 10, 1000684. [https://doi.org/10.3389/fcell.](https://doi.org/10.3389/fcell.2022.1000684)
136 [2022.1000684](https://doi.org/10.3389/fcell.2022.1000684)
- 137 Garyfallidis, E., Brett, M., Amirbekian, B., Rokem, A., Van Der Walt, S., Descoteaux, M.,
138 Nimmo-Smith, I., & Dipy Contributors. (2014). Dipy, a library for the analysis of diffusion
139 MRI data. *Frontiers in Neuroinformatics*, 8. <https://doi.org/10.3389/fninf.2014.00008>
- 140 Gohlke, C. (2025). *Cgohlke/tifffile*. <https://github.com/cgohlke/tifffile>
- 141 Jeppesen, N., Mikkelsen, L. P., Dahl, A. B., Christensen, A. N., & Dahl, V. A. (2021). Quan-
142 tifying effects of manufacturing methods on fiber orientation in unidirectional composites
143 using structure tensor analysis. *Composites Part A: Applied Science and Manufacturing*,
144 149, 106541. <https://doi.org/10.1016/j.compositesa.2021.106541>
- 145 Mekkaoui, C., Reese, T. G., Jackowski, M. P., Bhat, H., & Sosnovik, D. E. (2017). Diffusion
146 MRI in the heart. *NMR in Biomedicine*, 30(3), e3426. <https://doi.org/10.1002/nbm.3426>
- 147 Reichardt, M., Töpperwien, M., Khan, A., Alves, F., & Salditt, T. (2020). Fiber orientation
148 in a whole mouse heart reconstructed by laboratory phase-contrast micro-CT. *Journal of*
149 *Medical Imaging*, 7(02), 1. <https://doi.org/10.1117/1.JMI.7.2.023501>
- 150 Rocklin, M. (2015). *Dask: Parallel Computation with Blocked algorithms and Task Scheduling*.
151 126–132. <https://doi.org/10.25080/Majora-7b98e3ed-013>
- 152 Teh, I., McClymont, D., Zdora, M.-C., Whittington, H. J., Davidoiu, V., Lee, J., Lygate,
153 C. A., Rau, C., Zanette, I., & Schneider, J. E. (2016). Validation of diffusion tensor
154 MRI measurements of cardiac microstructure with structure tensor synchrotron radiation
155 imaging. *Journal of Cardiovascular Magnetic Resonance*, 19(1), 31. [https://doi.org/10.](https://doi.org/10.1186/s12968-017-0342-x)
156 [1186/s12968-017-0342-x](https://doi.org/10.1186/s12968-017-0342-x)
- 157 Tournier, J.-D., Smith, R., Raffelt, D., Tabbara, R., Dhollander, T., Pietsch, M., Christiaens,

- 158 D., Jeurissen, B., Yeh, C.-H., & Connelly, A. (2019). MRtrix3: A fast, flexible and open
159 software framework for medical image processing and visualisation. *NeuroImage*, 202,
160 116137. <https://doi.org/10.1016/j.neuroimage.2019.116137>
- 161 Van Der Walt, S., Colbert, S. C., & Varoquaux, G. (2011). The NumPy Array: A Structure
162 for Efficient Numerical Computation. *Computing in Science & Engineering*, 13(2), 22–30.
163 <https://doi.org/10.1109/MCSE.2011.37>
- 164 Yeh, F.-C. (2025). DSI Studio: An integrated tractography platform and fiber data hub for ac-
165 celerating brain research. *Nature Methods*. <https://doi.org/10.1038/s41592-025-02762-8>

DRAFT